

# CRACK FILL MELTER APPLICATORS

## RY10MA-ELITE



The RY10MA-Elite is the newest and most advanced melter-applicator available today. We built upon proven technology from earlier versions of the RY10MA-PRO but added many new features including RynoValve™, RynoDash™, Adjustable Controls as well as dozens of Major General Enhancements.



### SPECIFICATIONS

- Fluid Capacity**  
12.5 US Gallons
- Kettle Steel Thickness**  
14 Gauge
- Assembled Dimensions**  
49.9" x 29.3" x 48.8"
- Empty Weight**  
167.8 lbs / 76.3 kg
- Max Capacity Weight**  
290.3 lbs / 132.0 kg
- Fuel Type**  
Propane
- Max Fuel Pressure**  
5 psi
- Burner Type**  
50,000 BTU/hr  
Sealed Cast Iron Burner
- Valve Type**  
1.25" RynoValve™
- Agitation Type**  
On-the-fly

### INCREASED PRODUCTIVITY

- Melts crack sealant up to 50% faster than torch-fired models – apply up to 4,800 feet of crack filler per day.
- RynoValve™ requires virtually no preheating time and is ready to use as soon as you have hot sealant in the kettle, saving you time between jobs.

### EVEN MORE RELIABLE

- The enclosed burner design is shielded from the elements and virtually eliminates flame-outs caused by wind, which are common to torch-fired models.
- Two solid front casters allow the operator to maneuver over slanted surfaces with increased stability.

### EASIER TO OPERATE

- RynoDash™ allows you to easily ignite and monitor kettle temperatures from the comfort and convenience of the operator position.
- Side-by-side agitation, valve & band controls allow for continuous material agitation while you apply and spread sealant.

### SAFE AND COMFORTABLE

- Fully equipped with CSA / UL approved regulator and fuel lines provide precise control over fuel flow and kettle temperature.
- Handlebars are adjustable from 35"- 42" – optimize valve squeeze distance and spring tensions to reduce operator fatigue.